

TAYLORMADE JUNIOR SPEC EQUIPMENT



As your game grows, so should your equipment. TaylorMade introduces customized Junior Spec clubs, delivering premium in-line products fit for the intermediate junior golfer. It ensures high-level performance throughout the bag for the competitive or aspiring player dedicated to improving. Junior Spec clubs are the gateway to a higher level of golf.


DETAILS:

TaylorMade's Junior Spec offerings include more than a dozen shaft options and every in-line TaylorMade product. Shorter lengths and lighter swingweights make them fully customizable for junior golfers who have outgrown boxed sets, but are not quite ready for full-length equipment. Additional grip offerings and a range of loft/lie options allow for precision fit equipment that helps the golfer unlock their full potential.




STEALTH 2 DRIVERS

DRIVERS	LENGTH
STEALTH 2 PLUS+ DRIVER	40"
STEALTH 2 DRIVER	40"
STEALTH 2 HD DRIVER	40"




STEALTH 2 FAIRWAY

FAIRWAY	LENGTH
STEALTH 2 PLUS+ #3	38"
STEALTH 2 PLUS+ #5	37"
STEALTH 2 #3 / #3HL	38"
STEALTH 2 #5	37"
STEALTH 2 #7	36"
STEALTH 2 #9	35"



STEALTH 2 RESCUE

RESCUE	LENGTH
STEALTH 2 PLUS+ #3	36"
STEALTH 2 PLUS+ #4	35"
STEALTH 2 #3	36"
STEALTH 2 #4	35"
STEALTH 2 #5	34"
STEALTH 2 #6	33.5"
STEALTH 2 #7	33"




PUTTERS

ALL MODELS	LENGTH
	31"




P.700 SERIES
P•790 / P•770 / P•7MC / P•7MB

IRON	LENGTH
4	33.5"
5	33"
6	32.5"
7	32"
8	31.5"
9	31"
PW	30.75"
AW	30.5"



STEALTH IRONS

IRON	LENGTH
4	34.13"
5	33.5"
6	32.88"
7	32.25"
8	31.75"
9	31.25"
PW	30.75"
AW	30.5"
SW	30.25"
LW	30"



MILLED GRIND 3 **HI-TOE 3**

WEDGE	LENGTH
46	31"
50	30.75"
52	30.75"
54	30.5"
56	30.5"
58	30.25"
60	30.25"


ADJUSTMENTS AVAILABLE IN CUSTOM	
LOFT ADJUSTMENTS (IRONS/WEDGES)	+/-2°
LIE ADJUSTMENTS (IRONS/WEDGES)	+/-4°
LENGTH ADJUSTMENTS	-1° TO +2°

Loft and lies specifications mirror current stock specs for Mens / Womens


TAYLORMADE JUNIOR SPEC EQUIPMENT




SHAFTS - DRIVER / FAIRWAY




MODEL	FLEX
HZRDUS ORANGE	5.5




MODEL	FLEX
HELIUM NANOCORE	L
HELIUM NANOCORE	A
HELIUM NANOCORE	R




MODEL	FLEX
SPEEDER NX RED 50	A
SPEEDER NX RED 50	R



MODEL	FLEX
FUJIKURA VENTUS TR RED	R
FUJIKURA VENTUS TR RED	A




MODEL	FLEX
ALDILA ASCENT LADIES 45	L




MODEL	FLEX
PROJECT X EVENFLOW RIPTIDE CB 50	R
PROJECT X EVENFLOW RIPTIDE CB 50	A
PROJECT X EVENFLOW RIPTIDE CB 40	A
PROJECT X EVENFLOW RIPTIDE CB 40	L


SHAFTS - RESCUE




MODEL	FLEX
HZRDUS ORANGE	JR



MODEL	FLEX
SPEEDER NX RED 50 HY	A
SPEEDER NX RED 50 HY	R



MODEL	FLEX
FUJIKURA VENTUS TR RED	R
FUJIKURA VENTUS TR RED	A




MODEL	FLEX
ALDILA ASCENT LADIES 45	L

GRIPS




MODEL
GOLF PRIDE TOUR VELVET JUNIOR




MODEL
TAYLORMADE 360 RED JUNIOR


SHAFTS - IRONS




MODEL	FLEX
HZRDUS ORANGE	JR




MODEL	FLEX
FUJIKURA VENTUS RED 6	R
FUJIKURA VENTUS RED 5	A




MODEL	FLEX
ALDILA ASCENT LADIES 45	L



MODEL	FLEX
KBS MAX GRAPHITE 65	R
KBS MAX GRAPHITE 55	A
KBS MAX GRAPHITE 45	L



MODEL	FLEX
UST RECOIL 460 ESX	R (F3)
UST RECOIL 460 ESX	A (F2)
UST RECOIL 450 ESX	L (F1)



MODEL	FLEX
KBS 580	JNR

DRIVER RECOMMENDATION

HEIGHT	SHAFT LENGTH ADJUSTMENT	DRIVER LOFT	SHAFT FLEX
4'-4 1/4"	-1"	12°	Jnr Flex
4'5"-4'8"	STD	12°	Jnr Flex
4'9"-5'	+1"	10.5° / 12°	Jnr / L Flex
5'1"-5'4"	+2"	10.5° / 12°	L Flex / A Flex

FAIRWAY RECOMMENDATION

HEIGHT	SHAFT LENGTH ADJUSTMENT	FW LOFT	SHAFT FLEX
4'-4 1/4"	-1"	5W / 7W	Jnr Flex
4'5"-4'8"	STD	5W / 7W	Jnr Flex
4'9"-5'	+1"	5W	Jnr / L Flex
5'1"-5'4"	+2"	5W	L Flex / A Flex

RESCUE RECOMMENDATION

HEIGHT	SHAFT LENGTH ADJUSTMENT	RESCUE LOFT	SHAFT FLEX
4'-4 1/4"	-1"	#6-#7	Jnr Flex
4'5"-4'8"	STD	#6-#7	Jnr Flex
4'9"-5'	+1"	#5-#6	Jnr / L Flex
5'1"-5'4"	+2"	#5-#6	L Flex / A Flex

IRON RECOMMENDATION

HEIGHT	SHAFT LENGTH ADJUSTMENT	LOFT ADJUSTMENT	LIE ADJUSTMENT	SHAFT FLEX
4'-4 1/4"	-1"	2° Weak	4° Flat	Jnr Flex
4'5"-4'8"	STD	2° Weak	2° Flat	Jnr Flex
4'9"-5'	+1"	1° Weak	STD Lie	Jnr / L Flex
5'1"-5'4"	+2"	STD	STD Lie	L Flex / A Flex